

Instruction Sheet Ballistic Pendulum

Martin Henschke, 2004-06-21

art. no.: 650273

Copyright © 2006 Martin Henschke Gerätebau

Technical alterations reserved




Fig. 1: Components

- 1 Ball launcher (650267)
- 2 Back plate
- 3 Guide for swing pointer
- 4 Bearing screw
- 5 Counter bearing
- 6 Swing pointer
- 7 Angle scale
- 8 Pendulum
- 9 Ball catcher
- 10 Base plate
- 11 Table clamp
- 12 Knurled screw
- 13 Ramrod (delivered with 650267)
- 14 Extra weights, 2 pcs.

1. Safety instructions

This instruction sheet is concerned mainly with the ballistic pendulum. You should also read the instructions for the ball launcher 650267.

To check whether a ball is located in the ball launcher and the spring is cocked, only use the observation holes at the sides. Do not look into the barrel from the front. **Risk of injury!**

Never aim at people!

Protective goggles should be worn during the experiments.

The ball launcher should always be stored with the spring loose and with no ball in the barrel.

2. Description

The ballistic pendulum is for experiment-based determination of the launch velocity of a ball when it leaves the ball launcher. It is also possible to determine trajectories when the ball is launched horizontally or at an angle. Launch heights of 5, 10, 15, 20 or 30 cm can be selected easily with the aid of the drilled holes.

Thanks to the extreme lightness of the pendulum, the experiment can be performed using comparatively safe plastic balls instead of steel balls. Experiments involving inelastic collisions (quantitatively) and elastic collisions (qualitatively) can be evaluated. The velocity of the balls determined from trajectory and pendulum experiments typically agree to within about 3%.

Extra weights allow various pendulum travels to be investigated for constant speeds.

3. Operation and maintenance

First the ballistic pendulum is screwed to a stable bench by means of its clamp. The ball launcher is then screwed to the back plate (2) from behind either in a horizontal position in front of the pendulum as in Fig. 1 or as shown in Fig 3.

Tip: if the workbench is not stable enough, it may be that when the pendulum swings to its maximum extent and then swings back, it may jog the apparatus when striking the ball launcher, causing the swing pointer to be shifted out of line. If this happens, the pendulum should rather be stopped by hand.

Balls should always be loaded when the spring is not under tension by placing the sphere in loosely through the front of the plastic cylinder within the device. The sphere is then pushed down inside the barrel using the ramrod until the desired spring tension has been reached. The ramrod should not be removed too quickly, otherwise the suction its removal produces may pull the sphere out with it. The position of the sphere may only be checked using the observation holes. Never look into the barrel!

Before launching, ensure that no one is in the way of the trajectory. To launch, the cord of the launching lever is briefly pulled perpendicularly to the lever.

The pendulum (8) can be removed by undoing the bearing screw (4) and turned by 180° so that it is installed with the rear of the ball catcher (9) pointing towards the launcher (experiments on elastic collision). The counter bearing (5) is designed so that the pendulum hangs at a slight angle if the bearing screw is only light tightened. This means that the ball

catcher is not precisely in front of the launch aperture of the launcher. For this reason, the bearing screw should be tightened until the catcher and the launch aperture are in line.

After turning the pendulum round, or if necessary, the guide (3) for the swing pointer (6) should be adjusted so that the pointer just touches it when the pendulum is suspended at rest. The screw on the guide should only be finger-tightened to avoid the appearance of pressure on the pendulum rod.

Maintenance:

the ballistic pendulum principally requires no maintenance. If necessary some non-acid grease (Vaseline) can be applied to the bearing screw (4) and the knurled screw (12). Other than in the vicinity of the scale, the apparatus may be cleaned using acetone, ethanol (white spirit) or petroleum ether as required. Avoid submerging the equipment in water.

4. Experiment procedure and evaluation

4.1 Ballistic pendulum

4.1.1 Experiment setup

The experiment setup corresponds to Fig. 1 for experiments on inelastic collision. For experiments on elastic collisions, the pendulum should be turned round by 180° (cf. Section 3 „Operation“).

4.1.2 Experiment procedure

It is practical for these experiments to enter the experiment number, the spring tension (1, 2 or 3), the type of collision (inelastic „i“ or elastic „e“), the number of extra weights used and the measured angle φ . In order to obtain the most accurate experiment results, after one shot, a second should be performed with the swing pointer not having been reset to 0° in between. This minimizes the unavoidable frictional losses of the swing pointer.

Example experiment sequence:

No	Spring tension	Type of collision	Extra weights	Angle φ
1	1	i	0	17.5
2	2	i	0	25.0
3	3	i	0	36.0
4	1	i	2	9.5
5	2	i	2	13.5
6	3	i	2	19.0
7	1	e	0	29.5
8	2	e	0	42.0
9	3	e	0	60.0

4.1.3 Experiment evaluation

4.1.3.1 Inelastic collision

The following equation is valid for the swinging pendulum due to conservation of energy

$$E_{pot} = E_{kin} \quad (1)$$

where the potential energy is

$$E_{pot} = m_{tot}g\Delta h \quad (2)$$

Here is m_{tot} the total mass of the pendulum including the ball and any extra weights, g is the acceleration due to gravity and Δh is the difference in height of the center of gravity of the pendulum at rest and at the maximum extent of its swing. From the measured angle φ and the measured length l_S to the center of gravity according to Fig.2 the following is derived:

$$\Delta h = l_S(1 - \cos \varphi) \quad (3)$$




Fig. 2: Determining the required lengths. Distance between center of gravity and axis of rotation (l_S) should be measured including the ball and any additional weights when the collision is inelastic. To perform the measurement, the pendulum may, for example, be balanced on a ruler mounted on its side. The distance between the center of the ball and the axis of rotation is $l_K = 280$ mm.

The kinetic energy can be calculated from the moment of inertia I_{tot} relative to the axis of rotation and the maximum angular speed ω according to the equation

$$E_{kin} = \frac{1}{2} I_{tot} \omega^2. \quad (4)$$

If Equations 2 and 4 are inserted into Equation 1 and Δh eliminated using Equation 3 then the equation can be rearranged to:

$$\omega = \sqrt{\frac{2m_{tot}g l_S(1 - \cos \varphi)}{I_{tot}}} \quad (5)$$

However, we are not seeking ω , but the initial velocity of the ball v_0 . The relationship between the two values is given by the equation for the conservation of angular momentum directly before and after the collision:

$$L_K = L_{tot} \quad (6)$$

with the angular momentum of the ball

$$L_K = m_K l_K v_0 \quad (7)$$

before the collision and the total angular momentum

$$L_{tot} = I_{tot} \omega \quad (8)$$

after the collision. Inserting Eqs. 7 and 8 into Eq. 6 gives:

$$m_K l_K v_0 = I_{tot} \omega \quad (9)$$

Resolving this for ω and equating with Eq. 5 leads to the following relationship

$$v_0 = \frac{1}{m_K l_K} \sqrt{2I_{tot} m_{tot} g l_S (1 - \cos \varphi)} \quad (10)$$

The moment of inertia is in principle determined from the integral

$$I_{tot} = \int_m l^2 dm \quad (11)$$

where l is the distance of each mass element dm from the axis of rotation. Since in this case it is not the moment of inertia that we seek to derive I_{tot} can also be calculated from the period T of the pendulum (with ball and any extra weights). For a physical pendulum the following is valid for small deflections¹:

$$I_{tot} = m_{tot} g l_S \left(\frac{T}{2\pi} \right)^2 \quad (12)$$

This means that all the variables are now known or calculable. For the above example, the following table emerges:

No	m_K / kg	m_{tot} / kg	l_S / m	T / s	v_0 in m/s
1	0.00695	0.06295	0.218	1.01	3.39
2	0.00695	0.06295	0.218	1.01	4.82
3	0.00695	0.06295	0.218	1.01	6.88
4	0.00695	0.09795	0.252	1.07	3.51
5	0.00695	0.09795	0.252	1.07	4.98
6	0.00695	0.09795	0.252	1.07	6.99

The numeric values should be determined separately for every pendulum, since material and manufacturing tolerances mean that values may differ from one to another.

4.1.3.2 Elastic collision

For a swinging pendulum Eq. 5 is still valid for the motion after a collision, the only difference being that the moment of inertia I_P is determined without the ball but with any extra weights (pendulum mass m_P):

$$\omega = \sqrt{\frac{2m_P g l_S (1 - \cos \varphi)}{I_P}} \quad (13)$$

To determine the relationship between ω and the initial velocity v_0 both the conservation of angular momentum and the conservation of energy before and after the collision must now be used. The additional equation is required since the system has an additional degree of freedom in the ball velocity v_2 after the collision. As for Eq. 9, the following is true for the angular momentum:

$$m_K l_K v_0 = m_K l_K v_2 + I_P \omega$$

$$\Leftrightarrow$$

$$v_2 = v_0 - \frac{I_P \omega}{m_K l_K} \quad (14)$$

If this velocity v_2 is inserted into the equation for the conservation of energy

$$\frac{1}{2} m_K v_0^2 = \frac{1}{2} m_K v_2^2 + \frac{1}{2} I_P \omega^2 \quad (15)$$

¹ Recknagel, A.: Physik Mechanik, 3te Auflage, VEB Verlag Technik Berlin, 1958

When launching against a vertical wall (e.g. whiteboard) the radius of the ball (1.25 cm) should be subtracted from the distance between the point of launch and the wall to obtain the distance measurement x_M . The height measurement y_M relative to the launch height is given by the height of the impact on the wall minus 62.5 mm, 112.5 mm, 162.5 mm, 212.5 mm or 312.5 depending on the hole used.

4.1.2 Experiment procedure

It is practical for these experiments to note the experiment number, the spring tension (1, 2 or 3), the launch angle and the values x_M and y_M . Example:

No	Spring tension	launch angle $\varphi/^\circ$	distance x_M / cm	target height y_M / cm
1	1	0	171.3	-30
2	2	0	125.4	-30
3	3	0	86.9	-30
4	1	0	62.3	-15
5	2	0	90.5	-15
6	3	0	120.7	-15

4.1.3 Experiment evaluation

It is practical to take as the origin of the coordinate system the mid-point of the ball at the moment of launch. Then the following applies:

$$v_x = v_0 \cos \varphi \quad (17)$$

$$v_y = v_0 \sin \varphi \quad (18)$$

$$y = v_y t - \frac{1}{2} g t^2 \quad (19)$$

$$x = v_x t \quad (20)$$

From Eq. 20 $t = x/v_x$, whereby the time can be eliminated from Eq.19. If v_x and v_y are then eliminated from the resulting equation using Eqs. 17 and 18, the following is obtained

$$y = x \tan \varphi - x^2 \frac{g}{2v_0^2 \cos^2 \varphi} \quad (21)$$

This is the equation for the trajectory. In this equation only the launch velocity v_0 is unknown since the distances x and y were measured during the course of the experiments. If v_0 is calculated for the various experiments, the following results are obtained:

Spring tension	v_0 in m/s
1	3.53
2	5.10
3	6.85

The numbers are based on a total of 25 experiments, of which only 6 are explicitly listed in the above table. The trajectory can now be obtained from these using Eq. 21 and compared to the measured values. The result is shown in Fig. 4.




Fig. 4: Comparison of measurements and calculated curve, x = horizontal ball distance, y = vertical height, symbols = measured values (circles = spring tension 1, squares = spring tension 2, rhombuses = spring tension 3), lines = calculated trajectories